

DSM Fibre Intermediates Nyrin® 1525 (Glass), Dry

Category : Polymer , Thermoplastic , Nylon , Nylon 6

Material Notes:

Nyrin is a Block Copolymer of Nylon 6 and an elastomer with exceptional properties in impact resistance, fatigue and abrasion resistance.

Nyrin is processed via Reaction Injection Moulding (RIM) technology. Nyrin® is a registered trademark. Information provided by the manufacturer, Brueggemann Chemical.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DSM-Fibre-Intermediates-Nyrin-1525-Glass-Dry.php

Physical Properties	Metric	English	Comments
Density	1.322 g/cc	0.04776 lb/in ³	ISO 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	82	82	ISO 868
Tensile Strength, Ultimate	55.0 MPa	7980 psi	ISO 527
Elongation at Break	7.0 %	7.0 %	ISO 527
Modulus of Elasticity	3.75 GPa	544 ksi	ISO 527
Flexural Modulus	3.85 GPa	558 ksi	ISO 178
Izod Impact, Notched (ISO)	9.00 kJ/m ²	4.28 ft-lb/in ²	ISO 180
Charpy Impact, Notched	0.600 J/cm ²	2.86 ft-lb/in ²	DIN 53453
	0.500 J/cm ²	2.38 ft-lb/in ²	DIN 53453
	@Temperature -40.0 °C	@Temperature -40.0 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China