

## Daikin NEOFLON AC-5820 PFA Coating Powder, White

Category : Polymer , Thermoplastic , Fluoropolymer , PFA , Polyperfluoroalkoxyethylene, Molded/Extruded

### Material Notes:

NEOFLON PFA coating powder is designed for high build coatings having excellent resistance to chemical and corrosive environments. Description: 0.5-5 mm thickness. Processing Methods: Electrostatic spray coating, fluidized bed coating, roto molding, roto lining. Information provided by Daikin Industries.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Daikin-NEOFLON-AC-5820-PFA-Coating-Powder-White.php](http://www.lookpolymers.com/polymer_Daikin-NEOFLON-AC-5820-PFA-Coating-Powder-White.php)

Physical Properties	Metric	English	Comments
Bulk Density	0.830 g/cc	0.0300 lb/in <sup>3</sup>	
Thickness	500 - 5000 microns	19.7 - 197 mil	

Mechanical Properties	Metric	English	Comments
Coefficient of Friction	0.040 - 0.060	0.040 - 0.060	
Taber Abrasion, mg/1000 Cycles	<= 9.000	<= 9.000	Calculated using estimated density, 9.8 N load, cs-10 wheel

Thermal Properties	Metric	English	Comments
Flammability, UL94	V-0	V-0	
Oxygen Index	>= 95 %	>= 95 %	

Electrical Properties	Metric	English	Comments
Dielectric Constant	1.92 - 2.12	1.92 - 2.12	ASTM D150
	@Frequency 1000 Hz	@Frequency 1000 Hz	
Dielectric Constant	1.92 - 2.12	1.92 - 2.12	ASTM D150
	@Frequency 1e+6 Hz	@Frequency 1e+6 Hz	
Dissipation Factor	0.00010 - 0.00021	0.00010 - 0.00021	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China