

Dielectric Polymers NT-590 Polyimide Film Tape (discontinued **)

Category : Polymer , Adhesive , Film , Tape , Thermoset , Polyimide, TS , Silicone

Material Notes:

Crosslinked silicone adhesive with polyimide film backing. Features: U.L. recognized class 392°F High temperature resistant Clean tape removal Applications: For high temperature masking, protecting gold finger contacts during wave soldering, flame resistant electrical and thermal insulation, wire and cable wrap and wire bundle termination. Information provided by Dielectric Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dielectric-Polymers-NT-590-Polyimide-Film-Tape-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Thickness	25.4 microns	1.00 mil	Backing
	38.1 microns	1.50 mil	Adhesive

Mechanical Properties	Metric	English	Comments
Elongation at Break	60 %	60 %	
Peel Strength	0.2849 kN/m	1.625 pli	Adhesion
	5.26 kN/m	30.0 pli	Tensile

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 °C	500 °F	
	>= 288 °C	>= 550 °F	Shear Adhesive Failure (polyester failure)
	316 °C	600 °F	Intermittent
Minimum Service Temperature, Air	-73.3 °C	-100 °F	

Electrical Properties	Metric	English	Comments
Dielectric Breakdown	7500 V	7500 V	Dielectric Strength

Descriptive Properties	Value	Comments
Color	Amber	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China