

Dow Corning MOLYKOTE® G 68

Category : Fluid , Lubricant

Material Notes:

Semi-synthetic grease Information provided by Dow Corning

Order this product through the following link:

http://www.lookpolymers.com/polymer_Dow-Corning-MOLYKOTE-G-68.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.850 g/cc	0.850 g/cc	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Kinematic Viscosity	75 cSt	75 cSt	

Mechanical Properties	Metric	English	Comments
Four Ball Extreme Pressure, Weld Load	193.7 kg	427.1 lb (mass)	
Penetration P(60), 1/10 mm	250 - 280	250 - 280	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	140 °C	284 °F	
Minimum Service Temperature, Air	-30.0 °C	-22.0 °F	
Dropping Point	190 °C	374 °F	

Processing Properties	Metric	English	Comments
Shelf Life	60.0 Month	60.0 Month	

Descriptive Properties	Value	Comments
NLGI Number	2-3	
Water Resistant	yes	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China