

## **Dow Corning SYL-OFF® 297 ANCHORAGE ADDITIVE**

Category: Other Engineering Material, Additive/Filler for Polymer, Polymer, Adhesive

## **Material Notes:**

Syl-Off® 297 Anchorage Additive is a mixture of reactive silanes that is used to improve abrasion resistance and adhesion of the cured coating to the substrate. Information provided by Dow Corning

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Dow-Corning-SYL-OFF-297-ANCHORAGE-ADDITIVE.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.115 g/cc	1.115 g/cc	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Kinematic Viscosity	4.0 cSt	4.0 cSt	
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Storage Temperature	<= 30.0 °C	<= 86.0 °F	

Thermal Properties	Metric	English	Comments
Flash Point	51.0 °C	124 °F	closed cup

Optical Properties	Metric	English	Comments
Refractive Index	1.4248	1.4248	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Processing Properties	Metric	English	Comments
Shelf Life	36.0 Month	36.0 Month	

Descriptive Properties	Value	Comments
Active Content (%)	100	
Appearance	liquid	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China