

DuPont Elvax® 650Q Ethylene Vinyl Acetate

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate

Material Notes:

DuPont™ Elvax® 650Q is an ethylene-vinyl acetate copolymer resin for use in industrial applications. Applications: Elvax® 650Q resins can be used for the following applications: molding, compounding and extrusion; wire and cable; and adhesives, sealants, and wax blends. Information provided by DuPont™

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Elvax-650Q-Ethylene-Vinyl-Acetate.php

Physical Properties	Metric	English	Comments
Density	0.933 g/cc	0.0337 lb/in ³	ASTM D792-ISO 1183, ASTM D1505
Vinyl Acetate Content	12 %	12 %	
Melt Flow	8.0 g/10 min @Load 2.16 kg, Temperature 190 °C	8.0 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238, ISO 1133

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	93	93	ASTM D2240-ISO 868
Hardness, Shore D	43	43	ASTM D2240-ISO 868

Thermal Properties	Metric	English	Comments
Melting Point	95.0 °C	203 °F	DSC; ASTM D3417- ISO 3146
Vicat Softening Point	65.0 °C	149 °F	ASTM D1525, ISO 306
Brittleness Temperature	-100 °C	-148 °F	ASTM D746
Ring & Ball Softening Point	150 °C	302 °F	ASTM E28

Descriptive Properties	Value	Comments
Cloud Point in Paraffin Wax, °C	78	10% Elvax® in fully refined paraffin wax, 146 AMP. Incompatible at temperatures up to 177°C.

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China