

DuPont™ Fusabond® C190 Polymer Modifier

Category : Polymer , Thermoplastic , Adhesives, Sealants, and Coatings

Material Notes:

DuPont™ Fusabond® C190 is a anhydride modified ethylene vinyl acetate copolymer. Uses: Adhesives Pipe Coating Polymer Modifier

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Fusabond-C190-Polymer-Modifier.php

Physical Properties	Metric	English	Comments
Density	0.950 g/cc	0.0343 lb/in ³	ASTM D792, ISO 1183
Melt Flow	16 g/10 min @Load 2.16 kg, Temperature 190 °C	16 g/10 min @Load 4.76 lb, Temperature 374 °F	ASTM D1238, ISO 1133

Thermal Properties	Metric	English	Comments
Melting Point	71.0 °C	160 °F	ASTM D3418, ISO 3146

Processing Properties	Metric	English	Comments
Processing Temperature	<= 260 °C	<= 500 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China