

DuPont™ Kevlar® Aramid Pulp

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoset , Aramid

Material Notes:

Sold as highly fibrillated, short (0.5-1mm) fibers. Kevlar® pulps are chopped fibers that can be used as specialty additives to enhance performance by providing excellent reinforcement and viscosity control under shear stress. Kevlar® pulp is used in automotive brake pads, gaskets, automatic transmission papers, and as a viscosity control additive for adhesives and sealants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_DuPont-Kevlar-Aramid-Pulp.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.45 g/cc	1.45 g/cc	
Bulk Density	0.0481 - 0.112 g/cc	0.00174 - 0.00405 lb/in ³	
Specific Surface Area	7.0 - 11 m ² /g	7.0 - 11 m ² /g	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	350 °C	662 °F	
Minimum Service Temperature, Air	-200 °C	-328 °F	

Descriptive Properties	Value	Comments
Color	Yellow	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China