

Eliokem Sunigum® P95 Acrylate Elastomer

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Outstanding heat and UV resistance. Wide range of capabilities. Crosslinked polymer structure. CaCO₃ partitioning agent. Can be used in PVC, TPU, TPE/TPO and engineering plastic blends. Used in automotive (interior moldings, decorative profiles/spoilers, interior skins, oil and gas resistant parts), glazing gaskets, roofing membranes, flooring, footwear, cable jacketing, hoses and tubing, overmoldings, appliance gaskets/profiles, and synthetic leather. Information provided by Eliokem.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Eliokem-Sunigum-P95-Acrylate-Elastomer.php

Physical Properties	Metric	English	Comments
Density	1.12 g/cc	0.0405 lb/in ³	
Particle Size	1000 µm	1000 µm	Median
Mooney Viscosity	25 @Temperature 100 °C	25 @Temperature 212 °F	ML 1+4

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China