

Ensinger Tecatron® XP-61 Compression Molded PPS Compound, 25% Fiberglass and Mineral Filled

Category : Polymer , Thermoplastic , Polyphenylene Sulfide (PPS) , Polyphenylene Sulfide (PPS), Mineral/Glass-Fiber Filled

Material Notes:

Ensinger Special Polymers has over twenty different grades of TECATRON PPS available. Custom formulations can be blended to suit specific applications. Compression molding is amenable to short run production and yields products which are homogenous with low process stress. TECATRON PPS is a highly crystalline high-temperature thermoplastic with an excellent balance of cost, temperature resistance, strength, chemical resistance and flame retardance. TECATRON PPS is often used when long-term high-temperature performance and dimensional stability are a must, even in the presence of aggressive chemicals. Applications: Fuel

Injectors Manifolds Pumps Pistons Gears V-Packing Gaskets Bearings Information provided by Ensinger Special Polymers, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ensinger-Tecatron-XP-61-Compression-Molded-PPS-Compound-25-Fiberglass-and-Mineral-Filled.php

Physical Properties	Metric	English	Comments
Density	1.71 g/cc	0.0618 lb/in ³	ASTM D792
Filler Content	25 %	25 %	

Mechanical Properties	Metric	English	Comments
Tensile Strength	42.7 MPa	6200 psi	ASTM D638
Elongation at Break	0.70 %	0.70 %	ASTM D638
Tensile Modulus	6.89 GPa	1000 ksi	ASTM D638
Shear Strength	55.8 MPa	8100 psi	ASTM D732

Descriptive Properties	Value	Comments
Color	Black	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China