

Ensinger XP-132 Compression Molded PI Compound, 15% Graphite Filled

Category : Polymer , Thermoplastic , Polyimide, Thermoplastic , Thermoplastic Polyimide, Graphite Filled

Material Notes:

The XP-130 is an amorphous high performance thermoplastic with high permanent temperature and creep resistance as well as excellent bearing and wear properties, excellent long term thermal stability and creep resistance. The XP 130 Series of Polyimide is a non-melting high temperature thermoplastic with high strength over a wide range of temperatures, good long term thermal stability, minimal thermal expansion and excellent wear resistance along with good chemical resistance. Applications: Thermal & electrical insulators Switch Parts Vacuum Seals Plug Parts Chip Carriers Hot glass gripper fingers Balls for control valves Housing Parts Welding Equipment Information provided by Ensinger Special Polymers, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ensinger-XP-132-Compression-Molded-PI-Compound-15-Graphite-Filled.php

Physical Properties	Metric	English	Comments
Density	1.40 g/cc	0.0506 lb/in ³	ASTM D792
Filler Content	15 %	15 %	

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	119	119	ASTM D785
Tensile Strength	96.5 MPa	14000 psi	ASTM D638
Elongation at Break	3.0 %	3.0 %	ASTM D638
Flexural Strength	101 MPa	14700 psi	ASTM D790

Descriptive Properties	Value	Comments
Color	Dark Brown	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China