

ExxonMobil Escorene® LD-752 EVA Copolymer for Specialty Applications (discontinued **)

Category : Polymer , Thermoplastic , Ethylene Vinyl Acetate , Ethylene Vinyl Acetate; Molded/Extruded

Material Notes:

Data provided by the manufacturer, Exxon Chemical. A 28% vinyl acetate copolymer. Applications: Compound viscosity modifier; High flow applications.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Escorene-LD-752-EVA-Copolymer-for-Specialty-Applications-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.947 g/cc	0.0342 lb/in ³	Exxon Method
Apparent Bulk Density	0.577 g/cc	0.0208 lb/in ³	ASTM D1895 (B)
Melt Flow	150 g/10 min	150 g/10 min	Exxon Method

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	1.90 MPa	276 psi	ASTM D638
Elongation at Break	680 %	680 %	ASTM D638

Thermal Properties	Metric	English	Comments
Melting Point	64.0 °C	147 °F	Exxon Method
Vicat Softening Point	89.0 °C	192 °F	Softening Point, R&B; ASTM E-28

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China