

ExxonMobil Extra Hecta Super Mineral Mobil Cylinder Oil

Category : Fluid , Lubricant

Material Notes:

Mobil Cylinder oils are extra high performance high viscosity oils designed for use in enclosed worm gears operating at moderate to high speeds and temperatures, and where heavy loads, slow speeds or high temperatures demand high viscosity oils. They are also intended for use in all steam engine applications. They are formulated from high quality base stocks that are resistant to oxidation and thermal degradation, and the build-up of harmful deposits caused by the high operating temperatures of steam cylinders. They protect against rust and corrosion and provide good film strength and excellent lubricity and they are resistant to water washout. Mobil 600W Cylinder Oil, Mobil 600W Super Cylinder Oil and Mobil Extra Hecta Super Cylinder Oil are additized to enhance their frictional and load-carrying properties. All four members of the product family are widely used in worm gear applications, couplings and bearings, with viscosity grade depending on operating conditions. In steam applications Mobil 600W Super Cylinder Oil is recommended for saturated and superheated steam up to a temperature of 260°C. Mobil Extra Hecta Super Cylinder Oil and Mobil Extra Hecta Super Cylinder Oil Mineral may be used with superheated steam above 260°C. Mobil Extra Hecta Super Cylinder Oil Mineral has good demulsibility. Mobil Cylinder Oils can be applied both by drip feed cups and force feed mechanical lubricating devices. Mobil Cylinder Oils are the benchmark mineral product for worm gear OEMs and users, and are still recognised as leading products for steam cylinder applications. Mobil 600W Cylinder Oil is recommended for the following applications: The splash lubrication of enclosed worm gears operating at moderate to high speeds and temperatures. (Mobil 600 W Cylinder Oil); Steam cylinders, couplings, bearings, and break-in of compressor cylinders (Mobil 600 W Cylinder Oil); Mobil 600W Super Cylinder Oil and Mobil Extra Hecta Super Cylinder Oil are recommended for the above applications but under higher temperature and load conditions; Mobil Extra Hecta Super Cylinder Mineral is recommended where ready separation from condensate is essential, for example, where exhaust steam is used for process work; Mobil Extra Hecta Super Cylinder Mineral may also be used as a tempering oil for bath temperatures up to 290C

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Extra-Hecta-Super-Mineral-Mobil-Cylinder-Oil.php

Physical Properties	Metric	English	Comments
Density	0.920 g/cc	0.0332 lb/in ³	ASTM D4052
	@Temperature 15.6 °C	@Temperature 60.1 °F	
Viscosity Measurement	80	80	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	1000 cSt	1000 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	43 cSt	43 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	3.00 °C	37.4 °F	ASTM D97
Flash Point	288 °C	550 °F	ASTM D92

Descriptive Properties	Value	Comments
------------------------	-------	----------

Copper Strip Corrosion Descriptive Properties	18 Value	3 hrs @ 100°C Comments
--	-------------	---------------------------

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com
Email : sales@lookpolymers.com
Tel : +86 021-51131842
Mobile : +86 13061808058
Skype : lookpolymers
Address : United North Road 215,Fengxian District, Shanghai City,China