

ExxonMobil Exxsol™ D100 Dearomatized Fluid

Category : Fluid

Material Notes:

Availability: Africa & Middle East, Europe and South America Appearance: Clear/Transparent Liquid Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Exxsol-D100-Deaeromatized-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.818 g/cc @Temperature 15.0 °C	0.0296 lb/in ³ @Temperature 59.0 °F	ASTM D4052
Kinematic Viscosity	3.13 cSt	3.13 cSt	ASTM D445
Vapor Pressure	<= 0.000133 bar @Temperature 20.0 °C	<= 0.100 torr @Temperature 68.0 °F	ExxonMobil Method

Thermal Properties	Metric	English	Comments
Boiling Point	234 °C	453 °F	Initial; ASTM 1078
	267 °C	513 °F	Final; ASTM 1078
Flash Point	103 °C	217 °F	Method A; ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	172°F	Method E, ASTM D611
Aromatic Content	0.003	UV, ExxonMobil Method

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China