

ExxonMobil Isopar™ L (AP) Isoparaffin Fluid

Category : Fluid

Material Notes:

Product Description: A clear isoparaffin fluid, typically containing less than 1 ppm benzene and less than 1 ppm sulfur. **Appearance:** Clear/Transparent Liquid
Availability: Asia Pacific
Information provided by ExxonMobil

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Isopar-L-AP-Isoparaffin-Fluid.php

Physical Properties	Metric	English	Comments
Density	0.762 g/cc @Temperature 15.0 °C	0.0275 lb/in ³ @Temperature 59.0 °F	ASTM D4052
Kinematic Viscosity	1.61 cSt	1.61 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Boiling Point	184 °C	363 °F	Initial; ASTM D86
Flash Point	63.9 °C	147 °F	ASTM D93

Descriptive Properties	Value	Comments
Aniline Point	178°F	Method E, ASTM D611
Aromatic Content	<1%	ExxonMobil Method
Dry Point	390°F	ASTM D86

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China