

ExxonMobil Mobil Avrex M Turbo 201/1010

Category : Fluid , Lubricant

Material Notes:

Mobil Avrex M Turbo 201/1010 gas turbine lubricant is a combination of a proven aviation engine mineral oil base stock and an ashless additive package. The effective operating range for Mobil Avrex M Turbo 201/1010 is between -40°C and 121°C (-40°F and 250°F). The pour point is below -57°C (-70°F). Mobil Avrex M Turbo 201/1010 is recommended for older design aircraft gas turbine engines. The product is approved against U.S. Military Specification MIL-PRF-6081, Grade 1010. It should be used only in those turbine engines where the operating temperatures are within the capability range of mineral oil-based lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Mobil-Avrex-M-Turbo-2011010.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.885 g/cc	0.885 g/cc	15°C
Viscosity Measure	2818 cSt @Temperature -40.0 °C	2818 cSt @Temperature -40.0 °F	Kinematic Viscosity
Kinematic Viscosity at 40°C (104°F)	10.4 cSt	10.4 cSt	
Kinematic Viscosity at 100°C (212°F)	2.6 cSt	2.6 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-60.0 °C	-76.0 °F	
Flash Point	145 °C	293 °F	

Chemical Properties	Metric	English	Comments
Total Acid Number	0.030	0.030	mgKOH/g

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China