

ExxonMobil Mobilfluid 424

Category : Fluid , Lubricant

Material Notes:

Mobilfluid 424 is an extra high performance multipurpose tractor lubricant engineered to meet or exceed transmission and hydraulic fluid requirements. The advanced technology in Mobilfluid 424 is designed to optimise the performance of agricultural and commercial tractors operating in a wide range of environments and conditions. Mobilfluid 424 combines select base oils and an advanced additive package to deliver the varied lubricant performance properties required in severe duty applications of agricultural and construction equipment drive trains. It is particularly well suited for reducing wet brake and Power Take-Off (PTO) chatter. Heavy-duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTOs and hydrostatic drives; Recommended in off-highway industries including: agriculture, construction, and quarrying; Recommended for top-up and refill of systems; Suitable for commercial transmission applications requiring Type A (Suffix A), Dexron and Type F fluids. Do not use in passenger car automatic transmissions; May be used in applications requiring API GL-4 or SAE 80W grade lubricants in all gear applications except hypoid gear designs; Outstanding replacement for engine oils recommended for hydraulic and transmission systems

Order this product through the following link:

http://www.lookpolymers.com/polymer_ExxonMobil-Mobilfluid-424.php

Physical Properties	Metric	English	Comments
Density	0.880 g/cc @Temperature 15.0 °C	0.0318 lb/in ³ @Temperature 59.0 °F	ASTM D4052
Brookfield Viscosity	55000 cP @Temperature -35.0 °C	55000 cP @Temperature -31.0 °F	
Viscosity Measurement	145	145	Index; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	55 cSt	55 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	9.3 cSt	9.3 cSt	ASTM D445

Thermal Properties	Metric	English	Comments
Pour Point	-42.0 °C	-43.6 °F	ASTM D97
Flash Point	198 °C	388 °F	ASTM D92

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China