

## Fainplast Compounds GA 0248/4 Flexible PVC, Flame Retardant Sheathing

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Wire and Cable Grade

**Material Notes:**

Hydrocarbon resistant sheathing

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Fainplast-Compounds-GA-02484-Flexible-PVC-Flame-Retardant-Sheathing.php](http://www.lookpolymers.com/polymer_Fainplast-Compounds-GA-02484-Flexible-PVC-Flame-Retardant-Sheathing.php)

Physical Properties	Metric	English	Comments
Density	1.46 - 1.50 g/cc	0.0527 - 0.0542 lb/in <sup>3</sup>	ISO R 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	88 - 92	88 - 92	ISO R 868
Tensile Strength at Break	>= 15.0 MPa	>= 2180 psi	ISO R 527
Elongation at Break	>= 280 %	>= 280 %	ISO R 527

Descriptive Properties	Value	Comments
Thermal Stability (minutes)	70	CEI 20-34/3-2

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China