

## Fainplast Compounds PMP 0319/UV Flexible PVC, Extrusion Modified with PU

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Extruded

**Material Notes:**

Outdoor profiles PVC/PU anti-UV

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Fainplast-Compounds-PMP-0319UV-Flexible-PVC-Extrusion-Modified-with-PU.php](http://www.lookpolymers.com/polymer_Fainplast-Compounds-PMP-0319UV-Flexible-PVC-Extrusion-Modified-with-PU.php)

Physical Properties	Metric	English	Comments
Density	1.20 - 1.24 g/cc	0.0434 - 0.0448 lb/in <sup>3</sup>	ISO R 1183

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	82 - 86	82 - 86	ISO R 868
Tensile Strength at Break	20.0 MPa	2900 psi	ISO R 527
Elongation at Break	300 %	300 %	ISO R 527
Abrasion	50	50	[mm <sup>3</sup> ]; DIN 53516

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China