

Fibre Glast 71 Styrene Wax

Category : Fluid , Solvent

Material Notes:

#71 Styrene Wax is a 5% solution of paraffin dissolved in styrene that may be added to non waxed polyester resins and gel coats to prevent the prolonged tackiness associated with thin sections of polyesters. If the resin contains paraffins, the wax will rise to the surface and protect the curing resin from the inhibiting action of the air. However, if the resin is allowed to fully cure, the paraffins on the surface will prevent adhesion of further coats of resin and must be sanded off prior to additional applications. Fibre Glast recommends adding #71 at 5% for thin coatings. Use with #1040 Hi-Gloss Additive when performing repairs below the water line.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Fibre-Glast-71-Styrene-Wax.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.910 - 0.911 g/cc @Temperature 15.6 Â°C	0.910 - 0.911 g/cc @Temperature 60.0 Â°F	ASTM D891

Descriptive Properties	Value	Comments
Aldehyde (wt. %)	<0.02	ASTM D2119-87
Benzene (ppm)	<0.0001	ASTM D5135
Color (Pt. Co.)	10 (Typical)	ASTM D5386
Ethylbenzene (ppm)	<0.008	ASTM D5135
Inhibitor	0.001 - 0.0015	ASTM D4590
Peroxides (wt. %)	<0.01	ASTM D2340-82
Polymer (ppm)	<0.001	ASTM D2121-90
Styrene	>99.7	ASTM D5135
Total Chlorides (wt. %)	<0.0001	ASTM D4929
Total Sulfur (wt. %)	<0.0001	ASTM D3246

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China