Freudenberg Simrit Simriz® 488 High Temperature FFKT Perfluoroelastomer Compound

Category : Polymer , Thermoset , Fluoropolymer, TS , Thermoset Fluoroelastomer , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Perfluoro elastomers – or FFKM for short – have an ideal combination of characteristics, with their excellent chemical resistance, high level of temperature resistance, and high levels of elasticity. Simriz® perfluoro elastomers close the material gap between inelastic PTFE and elastomers, which have poor temperature and chemical resistance properties. With a fluoridation level of 72%, FFKM elastomers have a level of resistance close to that of pure PTFE at 76%. At the same time, FFKM materials are so elastic that they are excellently suited to both static and dynamic seals. Simrit offers ISC O-Rings which are specifically optimised with respect to flexibility at low temperatures, resistance to high temperatures, hardness, tensile strength, elongation, compression set, or color.Information provided by Freudenburg-NOK.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Freudenberg-Simrit-Simriz-488-High-Temperature-FFKT-Perfluoroelastomer-Compound.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	70	70	
Tensile Strength, Ultimate	20.1 MPa	2920 psi	
Elongation at Break	190 %	190 %	
Compression Set	28 %	28 %	70 hr
	@Temperature 275 °C	@Temperature 527 °F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	300 °C	572 °F	
Minimum Service Temperature, Air	0.000 °C	32.0 °F	

Descriptive Properties	Value	Comments
Color	lvory	
Water Resistance	3.2	70 h; 200°C

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers



Address : United North Road 215, Fengxian District, Shanghai City, China