

Garlock Klozure® Mill-Right® N NBR Oil Seal

Category: Polymer, Thermoset, Rubber or Thermoset Elastomer (TSE)

Material Notes:

A proprietary formulation of Nitrile (NBR). Engineered specifically for high-performance applications that demand the tightest sealing system, longest service life, and constant operation within harsh chemical environments. Information provided by Garlock Rubber Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_Garlock-Klozure-Mill-Right-N-NBR-Oil-Seal.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	80	80	
Coefficient of Friction	1.788	1.788	
Taber Abrasion, mg/1000 Cycles	150	150	ASTM D4060

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	93.3 °C	200 °F	Continuous
	121 °C	250 °F	Spike
Minimum Service Temperature, Air	-40.0 °C	-40.0 °F	

Processing Properties	Metric	English	Comments
Shelf Life	60.0 Month	60.0 Month	

Descriptive Properties	Value	Comments
Color	Black	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China