

Garlock Klokure® Mill-Right® V FKM Oil Seal

Category : Polymer , Thermoset , Fluoropolymer, TS , Thermoset Fluoroelastomer

Material Notes:

A proprietary formulation of Fluoroelastomer (FKM). Engineered specifically for high-performance applications that demand the tightest sealing system, longest service life, and constant operation within harsh chemical environments. Information provided by Garlock Rubber Technologies

Order this product through the following link:

http://www.lookpolymers.com/polymer_Garlock-Klokure-Mill-Right-V-FKM-Oil-Seal.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	76	76	
Coefficient of Friction	1.158	1.158	
Taber Abrasion, mg/1000 Cycles	40	40	ASTM D4060

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	204 Â°C	400 Â°F	Continuous
	232 Â°C	450 Â°F	Spike
Minimum Service Temperature, Air	-40.0 Â°C	-40.0 Â°F	

Processing Properties	Metric	English	Comments
Shelf Life	120 Month	120 Month	

Descriptive Properties	Value	Comments
Color	Green	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China