

Global GA-3245 High Density Polyethylene, Film Extrusion Grade (discontinued **)

Category : Polymer , Film , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Film Grade

Material Notes:

Description-opacity, medium high stiffness, good impact strength, good chemical resistanceApplications- shopping bags, packing bagsInformation provided by Global Polymers Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Global-GA-3245-High-Density-Polyethylene-Film-Extrusion-Grade-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.945 g/cc	0.0341 lb/in ³	ASTM D792
Melt Flow	0.10 g/10 min @Load 2.16 kg, Temperature 190 °C	0.10 g/10 min @Load 4.76 lb, Temperature 374 °F	Condition E; ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	37.0 MPa	5370 psi	ASTM D638
Tensile Strength, Yield	23.0 MPa	3340 psi	ASTM D638
Elongation at Break	1600 %	1600 %	ASTM D638

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China