

Global GPEI-210 10% Glass Filled Reinforced, Polyetherimide

Category : Polymer , Thermoplastic , Polyetherimide (PEI) , Polyetherimide (PEI), 10% Glass Fiber

Material Notes:

Information provided by Global Polymers Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Global-GPEI-210-10-Glass-Filled-Reinforced-Polyetherimide.php

Physical Properties	Metric	English	Comments
Density	1.34 g/cc	0.0484 lb/in ³	ASTM D792
Linear Mold Shrinkage	0.0060 cm/cm	0.0060 in/in	ASTM D955
Melt Flow	6.3 g/10 min @Load 6.60 kg, Temperature 337 °C	6.3 g/10 min @Load 14.6 lb, Temperature 639 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	114 MPa	16500 psi	ASTM D638
Flexural Modulus	4.48 GPa	650 ksi	ASTM D790
Izod Impact, Notched	0.534 J/cm	1.00 ft-lb/in	ASTM D256

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China