

Global N-3260 High Density Polyethylene, Yarn/Monofilament Grade (discontinued **)

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Extruded

Material Notes:

Description-opacity, medium high stiffness, good impact strength, good chemical resistanceApplications- ropes, fishing nets, wire & cable insulators, auto parts, pipesInformation provided by Global Polymers Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Global-N-3260-High-Density-Polyethylene-YarnMonofilament-Grade-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Density	0.956 g/cc	0.0345 lb/in ³	ASTM D792
Melt Flow	0.70 g/10 min @Load 2.16 kg, Temperature 190 °C	0.70 g/10 min @Load 4.76 lb, Temperature 374 °F	Condition E; ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	42.0 MPa	6090 psi	ASTM D638
Tensile Strength, Yield	29.0 MPa	4210 psi	ASTM D638

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China