

Global PEI-110 Easy Flow, Polyetherimide

Category : Polymer , Thermoplastic , Polyetherimide (PEI)

Material Notes:

Information provided by Global Polymers Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Global-PEI-110-Easy-Flow-Polyetherimide.php

Physical Properties	Metric	English	Comments
Density	1.27 g/cc	0.0459 lb/in ³	ASTM D792
Linear Mold Shrinkage	0.0060 cm/cm	0.0060 in/in	ASTM D955
Melt Flow	18 g/10 min @Load 6.60 kg, Temperature 337 °C	18 g/10 min @Load 14.6 lb, Temperature 639 °F	ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	102 MPa	14800 psi	ASTM D638
Flexural Modulus	3.10 GPa	450 ksi	ASTM D790
Izod Impact, Notched	0.320 J/cm	0.600 ft-lb/in	ASTM D256

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China