

Guarniflon TENFIL TF 200 Polytetrafluoroethylene Thread Sealant

Category : Polymer , Thermoplastic , Adhesives, Sealants, and Coatings , Fluoropolymer , PTFE

Material Notes:

TENFIL TF200 is a PTFE-based thread sealant in water dispersion, which increases the tightness of the threaded parts and prevents leakage of water. The product is intended for the assembly of fittings and threaded joints of different kinds of pipes. Information provided by Guarniflon®

Order this product through the following link:

http://www.lookpolymers.com/polymer_Guarniflon-TENFIL-TF-200-Polytetrafluoroethylene-Thread-Sealant.php

Physical Properties	Metric	English	Comments
Density	1.07 - 1.08 g/cc	0.0387 - 0.0390 lb/in ³	
Solids Content	50 - 55 %	50 - 55 %	
pH	4.0 - 6.0	4.0 - 6.0	
Brookfield Viscosity	11000 - 13000 cP	11000 - 13000 cP	
Surface Tension	38 dynes/cm	38 dynes/cm	

Thermal Properties	Metric	English	Comments
Boiling Point	100 °C	212 °F	
Clash Berg Stiffness Temperature	0.000 °C	32.0 °F	

Processing Properties	Metric	English	Comments
Dry Time	1.00 hour @Temperature 20.0 °C	1.00 hour @Temperature 68.0 °F	
Drying Air Flow Rate	9000 l/min @Temperature 80.0 °C, Time 80.0 sec	318 ft ³ /min (CFM) @Temperature 176 °F, Time 0.0222 hour	
	9000 l/min @Temperature 50.0 °C, Time 120 sec	318 ft ³ /min (CFM) @Temperature 122 °F, Time 0.0333 hour	
Shelf Life	12.0 Month @Temperature 4.00 - 35.0 °C	12.0 Month @Temperature 39.2 - 95.0 °F	

Descriptive Properties	Value	Comments
Chemical Resistance	Alcohol	Good
	Aliphatic Solvents	Good
	Aromatic Solvents	Moderate
	Ester	Moderate
	Glycols	Good
	Grease	Good
	Ketones	Moderate
	Oils	Good
Color	White	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China