

Gwent Electronic Materials C60903P5 Platinum Ink

Category : Fluid , Metal , Other Engineering Material , Ceramic/Metallic Coating

Material Notes:

Platinum Ink designed for use as an internal electrode ink. For use with PVB Tapes. Screen Printing Equipment: semi-automatic, manual
Screen Types: stainless steel, polyester, mesh 156-325 tpi
Substrate: Multilayer PVB tapes and foils
Information provided by Gwent Electronic Materials Ltd.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Gwent-Electronic-Materials-C60903P5-Platinum-Ink.php

Physical Properties	Metric	English	Comments
Solids Content	61 - 62 % @Temperature 800 Å°C	61 - 62 % @Temperature 1470 Å°F	
Viscosity	7000 - 11000 cP @Shear Rate 230 1/s, Temperature 25.0 Å°C	7000 - 11000 cP @Shear Rate 230 1/s, Temperature 77.0 Å°F	Haake VT 550 PK1.1Å°
Storage Temperature	20.0 Å°C	68.0 Å°F	sealed container

Processing Properties	Metric	English	Comments
Sintering Temperature	1100 - 1450 Å°C	2010 - 2640 Å°F	
Cure Time	15.0 min @Temperature 120 Å°C	0.250 hour @Temperature 248 Å°F	
Shelf Life	6.00 Month	6.00 Month	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China