

## **Hardwire 3x2-12-12 Medium Density Composite**

Category: Metal, Ferrous Metal, Carbon Steel, High Carbon Steel, Metal Foam, Mesh, or Honeycomb

## **Material Notes:**

The 3x2 Hardwire is a high carbon steel cord with a micro-fine brass or AO-brass (Adhesion Optimized) coating. The 3x2 wire cord is made by twisting 5 individual wire together - three straight filaments wrapped by 2 filaments (All filaments are 0.01378 in diameter) at a high twist angle. The result is an easy to handle cord that combines great engineering values with excellent economics. If the application is tension dominated choose the 3x2. Characteristics: Best properties in tensile applications. Excellent mix of engineering properties - Up to 8 KIPS/inch. Great stiffness, instant wet-ability, and excellent conformability. Works in all resins. Asymmetric shape acts like a screw and gives mechanical bonding characteristics Excellent fatigue properties in tension and in high-flex situations. Great choice for extrusion and pultrusion applications. All information provided by Hardwire, LLC.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Hardwire-3x2-12-12-Medium-Density-Composite.php

| Physical Properties | Metric    | English       | Comments         |
|---------------------|-----------|---------------|------------------|
| Density             | 2.32 g/cc | 0.0837 lb/in³ | Laminate Density |

| Mechanical Properties   | Metric   | English   | Comments          |
|-------------------------|----------|-----------|-------------------|
| Modulus of Elasticity   | 42.1 GPa | 6100 ksi  | Effective Modulus |
| Flexural Yield Strength | 607 MPa  | 88000 psi | Sheet Stress      |

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China