

Haynes 230[®] alloy plate, 1000 hours exposure at 649^{°C} (1200^{°F})

Category : Metal , Nonferrous Metal , Nickel Alloy , Superalloy

Material Notes:

Excellent high-temperature strength, outstanding resistance to oxidizing environments up to 1149^{°C}, premier resistance to nitriding environments, and excellent long-term thermal stability. Applications include combustion cans, transition ducts, flameholders, thermocouple sheaths and other gas turbine components; used for catalyst grid supports in ammonia burners, high-strength thermocouple protection tubes, high-temperature heat exchangers, ducts, high-temperature bellows; furnace retorts, chains and fixtures, burner flame shrouds, recuperator internals, dampers, nitriding furnace internals, heat-treating baskets, grates, trays, sparger tubes, and cyclone internals. Data provided by the manufacturer, Haynes International, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Haynes-230-alloy-plate-1000-hours-exposure-at-649C-1200F.php

| Physical Properties | Metric | English | Comments |
|----------------------------|--|--|------------|
| Density | 8.97 g/cc | 0.324 lb/in ³ | at RT |
| Mechanical Properties | Metric | English | Comments |
| Tensile Strength, Ultimate | 895 MPa | 130000 psi | |
| Tensile Strength, Yield | 440 MPa @Strain 0.200 % | 63800 psi @Strain 0.200 % | |
| Elongation at Break | 43 % | 43 % | in 50.8 mm |
| Modulus of Elasticity | 211 GPa | 30600 ksi | RT |
| | 150 GPa @Temperature 1000 ^{°C} | 21800 ksi @Temperature 1830 ^{°F} | |
| | 157 GPa @Temperature 900 ^{°C} | 22800 ksi @Temperature 1650 ^{°F} | |
| | 164 GPa @Temperature 800 ^{°C} | 23800 ksi @Temperature 1470 ^{°F} | |
| | 171 GPa @Temperature 700 ^{°C} | 24800 ksi @Temperature 1290 ^{°F} | |
| | 177 GPa @Temperature 600 ^{°C} | 25700 ksi @Temperature 1110 ^{°F} | |

| Mechanical Properties | Metric | English | Comments |
|-----------------------|--------------------------------|----------------------------------|----------|
| | 194 GPa @Temperature 500 °C | 26700 ksi @Temperature 932 °F | |
| | 190 GPa @Temperature 400 °C | 27600 ksi @Temperature 752 °F | |
| | 196 GPa @Temperature 300 °C | 28400 ksi @Temperature 572 °F | |
| | 202 GPa @Temperature 200 °C | 29300 ksi @Temperature 392 °F | |
| | 207 GPa @Temperature 100 °C | 30000 ksi @Temperature 212 °F | |
| Charpy Impact | 46.0 J | 33.9 ft-lb | |

| Thermal Properties | Metric | English | Comments |
|--------------------|---|--|----------|
| CTE, linear | 12.7 Åµm/m-°C @Temperature 25.0 - 100 °C | 7.06 Åµin/in-°F @Temperature 77.0 - 212 °F | |
| | 13.0 Åµm/m-°C @Temperature 25.0 - 200 °C | 7.22 Åµin/in-°F @Temperature 77.0 - 392 °F | |
| | 13.3 Åµm/m-°C @Temperature 25.0 - 300 °C | 7.39 Åµin/in-°F @Temperature 77.0 - 572 °F | |
| | 13.7 Åµm/m-°C @Temperature 25.0 - 400 °C | 7.61 Åµin/in-°F @Temperature 77.0 - 752 °F | |
| | 14.0 Åµm/m-°C @Temperature 25.0 - 500 °C | 7.78 Åµin/in-°F @Temperature 77.0 - 932 °F | |
| | 14.4 Åµm/m-°C @Temperature 25.0 - 600 °C | 8.00 Åµin/in-°F @Temperature 77.0 - 1110 °F | |
| | 14.8 Åµm/m-°C @Temperature 25.0 - 700 °C | 8.22 Åµin/in-°F @Temperature 77.0 - 1290 °F | |
| | 15.2 Åµm/m-°C | 8.44 Åµin/in-°F | |

| Thermal Properties | @Temperature 25.0 - Metric 800 °C | @Temperature 77.0 - English 1490 °F | Comments |
|------------------------|---|---|----------|
| | 15.7 Åµm/m-Å°C | 8.72 Åµin/in-Å°F | |
| | @Temperature 25.0 - 900 °C | @Temperature 77.0 - 1650 °F | |
| | 16.1 Åµm/m-Å°C | 8.94 Åµin/in-Å°F | |
| | @Temperature 25.0 - 1000 °C | @Temperature 77.0 - 1830 °F | |
| Specific Heat Capacity | 0.397 J/g-Å°C | 0.0949 BTU/lb-Å°F | RT |
| | 0.419 J/g-Å°C | 0.100 BTU/lb-Å°F | |
| | @Temperature 100 °C | @Temperature 212 °F | |
| | 0.435 J/g-Å°C | 0.104 BTU/lb-Å°F | |
| | @Temperature 200 °C | @Temperature 392 °F | |
| | 0.448 J/g-Å°C | 0.107 BTU/lb-Å°F | |
| | @Temperature 300 °C | @Temperature 572 °F | |
| | 0.465 J/g-Å°C | 0.111 BTU/lb-Å°F | |
| | @Temperature 400 °C | @Temperature 752 °F | |
| | 0.473 J/g-Å°C | 0.113 BTU/lb-Å°F | |
| | @Temperature 500 °C | @Temperature 932 °F | |
| | 0.486 J/g-Å°C | 0.116 BTU/lb-Å°F | |
| | @Temperature 600 °C | @Temperature 1110 °F | |
| | 0.574 J/g-Å°C | 0.137 BTU/lb-Å°F | |
| | @Temperature 700 °C | @Temperature 1290 °F | |
| | 0.595 J/g-Å°C | 0.142 BTU/lb-Å°F | |
| | @Temperature 800 °C | @Temperature 1470 °F | |
| | 0.609 J/g-Å°C | 0.146 BTU/lb-Å°F | |
| | @Temperature 900 °C | @Temperature 1650 °F | |
| | 0.617 J/g-Å°C | 0.147 BTU/lb-Å°F | |
| | @Temperature 1000 °C | @Temperature 1830 °F | |
| Thermal Conductivity | 8.90 W/m-K | 61.8 BTU-in/hr-ft²-Å°F | RT |

| Thermal Properties | Metric 10 ⁻⁴ W/m-K | English U-in/hr-ft ² - Â°F | Comments |
|--------------------|----------------------------------|---|----------|
| | @Temperature 100 Â°C | @Temperature 212 Â°F | |
| | 12.4 W/m-K | 86.1 BTU-in/hr-ft ² - Â°F | |
| | @Temperature 200 Â°C | @Temperature 392 Â°F | |
| | 14.4 W/m-K | 99.9 BTU-in/hr-ft ² - Â°F | |
| | @Temperature 300 Â°C | @Temperature 572 Â°F | |
| | 16.4 W/m-K | 114 BTU-in/hr-ft ² -Â°F | |
| | @Temperature 400 Â°C | @Temperature 752 Â°F | |
| | 18.4 W/m-K | 128 BTU-in/hr-ft ² -Â°F | |
| | @Temperature 500 Â°C | @Temperature 932 Â°F | |
| | 20.4 W/m-K | 142 BTU-in/hr-ft ² -Â°F | |
| | @Temperature 600 Â°C | @Temperature 1110 Â°F | |
| | 22.4 W/m-K | 155 BTU-in/hr-ft ² -Â°F | |
| | @Temperature 700 Â°C | @Temperature 1290 Â°F | |
| | 24.4 W/m-K | 169 BTU-in/hr-ft ² -Â°F | |
| | @Temperature 800 Â°C | @Temperature 1470 Â°F | |
| | 26.4 W/m-K | 183 BTU-in/hr-ft ² -Â°F | |
| | @Temperature 900 Â°C | @Temperature 1650 Â°F | |
| | 28.4 W/m-K | 197 BTU-in/hr-ft ² -Â°F | |
| | @Temperature 1000 Â°C | @Temperature 1830 Â°F | |
| Melting Point | 1301 - 1371 Â°C | 2374 - 2500 Â°F | |
| Solidus | 1301 Â°C | 2374 Â°F | |
| Liquidus | 1371 Â°C | 2500 Â°F | |

| Component Elements Properties | Metric | English | Comments |
|-------------------------------|------------|------------|----------|
| Aluminum, Al | 0.30 % | 0.30 % | |
| Boron, B | <= 0.015 % | <= 0.015 % | |

| Carbon, C Component Elements Properties | 0.10 % Metric | 0.10 % English | Comments |
|---|---------------|----------------|----------|
| Chromium, Cr | 22 % | 22 % | |
| Cobalt, Co | <= 5.0 % | <= 5.0 % | |
| Iron, Fe | <= 3.0 % | <= 3.0 % | |
| Lanthanum, La | 0.020 % | 0.020 % | |

| Electrical Properties | Metric | English | Comments |
|------------------------|----------------------|----------------------|----------|
| Electrical Resistivity | 0.000125 ohm-cm | 0.000125 ohm-cm | RT |
| | 0.000125 ohm-cm | 0.000125 ohm-cm | |
| | @Temperature 1000 °C | @Temperature 1830 °F | |
| | 0.0001258 ohm-cm | 0.0001258 ohm-cm | |
| | @Temperature 100 °C | @Temperature 212 °F | |
| | 0.0001265 ohm-cm | 0.0001265 ohm-cm | |
| | @Temperature 200 °C | @Temperature 392 °F | |
| | 0.0001271 ohm-cm | 0.0001271 ohm-cm | |
| | @Temperature 900 °C | @Temperature 1650 °F | |
| | 0.0001273 ohm-cm | 0.0001273 ohm-cm | |
| | @Temperature 300 °C | @Temperature 572 °F | |
| | 0.0001284 ohm-cm | 0.0001284 ohm-cm | |
| | @Temperature 400 °C | @Temperature 752 °F | |
| | 0.0001291 ohm-cm | 0.0001291 ohm-cm | |
| | @Temperature 800 °C | @Temperature 1470 °F | |
| | 0.0001302 ohm-cm | 0.0001302 ohm-cm | |
| | @Temperature 500 °C | @Temperature 932 °F | |
| | 0.0001307 ohm-cm | 0.0001307 ohm-cm | |
| | @Temperature 700 °C | @Temperature 1290 °F | |
| | 0.0001312 ohm-cm | 0.0001312 ohm-cm | |
| | @Temperature 600 °C | @Temperature 1110 °F | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China