

Henkel Hysol PL 795SF Composite Surfacing Film

Category : Polymer , Film

Material Notes:

Modified epoxy film specifically formulated to improve the surface appearance of composite honeycomb structures. Excellent surface appearance; reduced pinholing, extra finishing. Superior out-time. Good building tack; repositionable on itself, prepregs, tools.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Henkel-Hysol-PL-795SF-Composite-Surfacing-Film.php

Physical Properties	Metric	English	Comments
Storage Temperature	-18.0 Â°C	-0.400 Â°F	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	177 Â°C	351 Â°F	

Processing Properties	Metric	English	Comments
Cure Time	60.0 min	1.00 hour	
	@Temperature 177 Â°C	@Temperature 351 Â°F	
	90.0 min	1.50 hour	
	@Temperature 121 Â°C	@Temperature 250 Â°F	

Descriptive Properties	Value	Comments
Out-Time (days)	100	at 25Â°C

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China