

## Ineos ABS Lustran<sup>®</sup> SAN DN79 SAN Grade

Category : Polymer , Thermoplastic , SAN Polymer , Styrene Acrylonitrile (SAN), Molded

### Material Notes:

Lustran<sup>®</sup> SAN DN79 is a natural color, styrene-acrylonitrile copolymer supplied in pellet form. It is designed for used in compounding.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ineos-ABS-Lustran-SAN-DN79-SAN-Grade.php](http://www.lookpolymers.com/polymer_ineos-ABS-Lustran-SAN-DN79-SAN-Grade.php)

Physical Properties	Metric	English	Comments
Melt Flow	7.5 g/10 min @Load 3.80 kg, Temperature 230 Â°C	7.5 g/10 min @Load 8.38 lb, Temperature 446 Â°F	ASTM-D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	79.3 MPa	11500 psi	ASTM-D638
Flexural Strength	96.5 MPa	14000 psi	at Fail; ASTM-D790
Flexural Modulus	3.62 GPa	525 ksi	ASTM-D790
Izod Impact, Unnotched	3.63 J/cm	6.80 ft-lb/in	ASTM-D256

Thermal Properties	Metric	English	Comments
Vicat Softening Point	111 Â°C @Load 1.00 kg	232 Â°F @Load 2.20 lb	120Â°C/hour; ASTM-D1525

Descriptive Properties	Value	Comments
Acrylonitrile Content (%)	32.5	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China