

Ipiranga Petrochem GP 100 OR HDPE

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE

Material Notes:

The resin GP 100 OR is a high density polyethylene compounding with high molar mass, specially developed for the manufacturing of extruded pipes for gas distribution. It is produced with bimodal technology, has excellent mechanical properties and very high stress cracking resistance and resistance to internal pressure. This resin is manufactured in orange color and with additives against the action of ultraviolet radiation. Applications: Pressure pipes for gas distribution

Order this product through the following link:

http://www.lookpolymers.com/polymer_ipiranga-Petrochem-GP-100-OR-HDPE.php

Physical Properties	Metric	English	Comments
Density	0.950 - 0.952 g/cc	0.0343 - 0.0344 lb/in ³	ASTM D792-00
ESCR 100% Igepal®	>= 1000 hour	>= 1000 hour	ASTM D1693-01
Melt Flow	6.1 - 7.5 g/10 min	6.1 - 7.5 g/10 min	ASTM D1238-04
	0.16 - 0.22 g/10 min @Load 5.00 kg, Temperature 190 °C	0.16 - 0.22 g/10 min @Load 11.0 lb, Temperature 374 °F	ASTM D1238-04

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	10.0 MPa	1450 psi	ISO 9080-03
Flexural Modulus	0.850 GPa	123 ksi	2% secant; ASTM D790-02
Izod Impact, Notched	3.20 J/cm	5.99 ft-lb/in	ASTM D256-03

Descriptive Properties	Value	Comments
Slow Crack Growth (h)	>165	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China