

## **Kazanorgsintez 153-05K Cable Composition Based on Low Density Polyethylene**

Category: Polymer, Thermoplastic, Polyethylene (PE), LDPE, Low Density Polyethylene (LDPE), Wire/Cable Grade

## **Material Notes:**

Production Method: Produced in the form of pellets (natural or black colored) on the bases of basic 10204-003, 15303-003, 15313-003.

Application: Designed to apply isolation, cable covers and cable shielding by extrusion method. Information Provided by Kazanorgsintez

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Kazanorgsintez-153-05K-Cable-Composition-Based-on-Low-Density-Polyethylene.php

Physical Properties	Metric	English	Comments	
Density	0.9185 - 0.924 g/cc	0.03318 - 0.0334 lb/in³		
Environmental Stress Crack Resistance	>= 500 hour	>= 500 hour		
Melt Flow	0.21 - 0.39 g/10 min	0.21 - 0.39 g/10 min	±8%	
	@Load 21.6 kg	@Load 47.6 lb	A10%	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	>= 9.80 MPa	>= 1420 psi	
Elongation at Break	>= 600 %	>= 600 %	
Tear Strength Test	>= 13.7	>= 13.7	MPa

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	>= 200 °C	>= 392 °F	
	@Time >=900 sec	@Time >=0.250 hour	

Electrical Properties	Metric	English	Comments	
Dielectric Constant	<= 2.3	<= 2.3		
Dielectric Constant	@Frequency 1000 Hz	@Frequency 1000 Hz		
Dielectric Strength	>= 40.0 kV/mm	>= 1020 kV/in	Sample of 1 mm thickness, Alternating current	
	@Frequency 50.0 Hz	@Frequency 50.0 Hz		
Dissipation Factor	<= 0.00030	<= 0.00030		
	@Frequency 1000 Hz	@Frequency 1000 Hz		

Descriptive Properties	Value	Comments	
------------------------	-------	----------	--



Descriptive Properties	Value	Comments
	3	Superior Quality

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China