

Kazanorgsintez 158BK-15 Low Density Polyethylene Composite

Category : Polymer , Thermoplastic , Polyethylene (PE) , LDPE

Material Notes:

Production Method: Produced from low density polyethylene grades 15803-020 and 15813-020. Application: Designed for production of sealing coatings on industrial items. Information Provided by Kazanorgsintez

Order this product through the following link:

http://www.lookpolymers.com/polymer_Kazanorgsintez-158BK-15-Low-Density-Polyethylene-Composite.php

Mechanical Properties	Metric	English	Comments
Elongation at Break	>= 300 %	>= 300 %	
Tear Strength Test	>= 6.5	>= 6.5	MPa

Thermal Properties	Metric	English	Comments
Softening Point	105 - 120 Â°C	221 - 248 Â°F	
Minimum Service Temperature, Air	<= -60.0 Â°C	<= -76.0 Â°F	

Descriptive Properties	Value	Comments
Amount of impurities [pcs]	50	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China