

Kazanorgsintez E-5 Petroleum Resin

Category: Other Engineering Material, Additive/Filler for Polymer

Material Notes:

Production Method: Obtained as a by-product in the process of hydrocarbon gas pyrolysis on ethylene production plants. Application:

Feedstock for production of motor fuel, solvents and aromatic hydrocarbons. Information Provided by Kazanorgsintez

Order this product through the following link:

http://www.lookpolymers.com/polymer_Kazanorgsintez-E-5-Petroleum-Resin.php

| Physical Properties | Metric | English | Comments |
|---------------------|-------------------------|----------------------|----------|
| Density | >= 0.750 g/cc | >= 0.0271 lb/in³ | |
| | @Temperature 20.0 °C | @Temperature 68.0 °F | |

| Thermal Properties | Metric | English | Comments |
|--------------------|------------|------------|----------|
| Boiling Point | >= 35.0 °C | >= 95.0 °F | Initial |
| | <= 230 °C | <= 446 °F | End |

| Component Elements Properties | Metric | English | Comments | |
|-------------------------------|----------|----------|----------|--|
| Free Water | <= 1.0 % | <= 1.0 % | | |

| Descriptive Properties | Value | Comments |
|---------------------------|--|---|
| Appearance | Liquid of light-yellow to brown color, free of mechanical impurities | |
| Mass Content (%) | 30 | Mass content of benzene |
| | 60 | Mass content of aromatic hydrocarbons (C6-C8) |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China