

## Loctite® 542 Fine Threads Thread Sealant

Category : Polymer , Adhesive , Thermoset

### Material Notes:

Thread Sealers Loctite® Liquid Thread Sealants seal and secure metal pipes and fittings, filling the space between threaded metal parts, and hardening to prevent leakage. Designed for low and high pressure applications, liquid thread sealants seal instantly for low pressure testing. When fully cured, they seal to the burst strength of most piping systems. Loctite® Pre-Applied Thread Sealants are dry-to-the-touch films applied to threaded fittings by fitting suppliers and process centers located throughout North America. Pre-applied thread sealants are ideal for OEMs because they can improve speed of assembly and ensure quality by eliminating on-line dispensing of sealants. Loctite® 542 Fine Threads Thread Sealant A liquid sealant recommended for sealing the fine threads of hydraulic and pneumatic connectors. Seals operating pressures to 10,000 psi. Recommended Primer: 7649 (N) Typical Use: Fine Threads

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Loctite-542-Fine-ThreadsThread-Sealant.php](http://www.lookpolymers.com/polymer_Loctite-542-Fine-ThreadsThread-Sealant.php)

Physical Properties	Metric	English	Comments
Density	1.06 g/cc	0.0383 lb/in³	
Viscosity	525 - 1850 cP	525 - 1850 cP	Thixotropic

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-53.9 °C	-65.0 °F	

Descriptive Properties	Value	Comments
Color	Brown	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China