

Lord Adhesives Chemglaze® 9974 Roller Additive

Category: Other Engineering Material, Additive/Filler for Polymer

Material Notes:

Chemglaze® thinners are formulated with urethane grade solvents and are used to reduce viscosity, aid bubble release, minimize orange peel, and make application easier. Chemglaze 9974 additive is used for bubble release when using a roller in some Chemglaze Z-Line and V-Line coatings. An additive for use with Chemglaze Z-Line and VLine coatings to permit roller application. Aids bubble release, minimizes air entrapment, reduces pigment bonding and improves surface wetting and flow. Suggested use per gallon of Chemglaze is 0.5 - 1.0 fluid ounce for clear, and 1.5 - 2.0 fluid ounces for pigmented. Stir or shake well before use. All information provided by Lord.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lord-Adhesives-Chemglaze-9974-Roller-Additive.php

Physical Properties	Metric	English	Comments
Density	0.810 g/cc	0.0293 lb/in³	

Thermal Properties	Metric	English	Comments
Flash Point	49.0 °C	120 °F	Seta, Closed Cup

Electrical Properties	Metric	English	Comments
Surface Resistance	1.00e+7 ohm	1.00e+7 ohm	

Processing Properties	Metric	English	Comments
	12.0 Month	12.0 Month	
Shelf Life	@Temperature 0.000 - 32.0 °C	@Temperature 32.0 - 89.6 °F	

Descriptive Properties	Value	Comments
Appearance	Slightly hazy to cloudy	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China