

Lubriplate 1241 Lithium-Polymer Type Multi-Purpose Grease

Category: Fluid, Lubricant, Lithium Gellant

Material Notes:

Highly water resistant and tacky, they are designed for applications were the grease is subjected to heavy pressure and shock loads. This series is available in 3 NLGI densities for a wide range of applications and temperatures. Applications: Centralized or hand greasing. 1240 Series Greases are available in Cartridges, Cans, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-1241-Lithium-Polymer-Type-Multi-Purpose-Grease.php

| Physical Properties | Metric | English | Comments |
|--|----------|----------|----------|
| Saybolt Viscosity at 100°F | 1250 SUS | 1250 SUS | |
| Kinematic Viscosity at 40°C (104°F) | 237 cSt | 237 cSt | |

| Mechanical Properties | Metric | English | glish Comments | |
|----------------------------|--------|---------|------------------------|--|
| Penetration P(0), 1/10 mm | 310 | 310 | Unknown Amount of Work | |
| Penetration P(60), 1/10 mm | 340 | 340 | Unknown Amount of Work | |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|---------|-------------------|
| Minimum Service Temperature, Air | -15.0 °C | 5.00 °F | Approx. Cold test |
| Dropping Point | 204 °C | 400 °F | ASTM Test |

| Descriptive Properties | Value | Comments |
|--------------------------------------|-------|----------|
| Antiwear (AW)/ Extreme Pressure (EP) | AW/EP | |
| NLGI Grade | 1 | |
| Rust/Oxidative Additives | YES | |
| Water Resistant | YES | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China