Lubriplate 1242 Lithium-Polymer Type Multi-Purpose Grease

Category : Fluid , Lubricant , Lithium Gellant

Material Notes:

Highly water resistant and tacky, they are designed for applications were the grease is subjected to heavy pressure and shock loads. This series is available in 3 NLGI densities for a wide range of applications and temperatures. Applications: Heavy-duty construction equipment. 1240 Series Greases are available in Cartridges, Cans, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link: http://www.lookpolymers.com/polymer_Lubriplate-1242-Lithium-Polymer-Type-Multi-Purpose-Grease.php

Physical Properties	Metric	English	Comments	
Saybolt Viscosity at 100°F	1250 SUS	1250 SUS		
Kinematic Viscosity at 40°C (104°F)	237 cSt	237 cSt		

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	265	265	Unknown Amount of Work
Penetration P(60), 1/10 mm	295	295	Unknown Amount of Work

Thermal Properties	Metric	English	Comments	
Minimum Service Temperature, Air	-9.44 °C	15.0 °F	Approx. Cold test	
Dropping Point	218 °C	425 °F	ASTM Test	

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW/EP	
NLGI Grade	2	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China