

Lubriplate 68 SYN High Temp 100% Ester-Based Multi-Purpose Synthetic Fluid

Category : Fluid , Lubricant

Material Notes:

These 100% ester-based synthetic lubricants are recommended for applications that are exposed to high operating temperatures and must maintain a clean lubricated surface. Available in ISO viscosity grades 68 and 220. Proven successful in applications in excess of 600Â°F/316Â°C. Applications: Recommended for use on bakery oven chains, drying oven chains, tenter frame chains, heat treating chains, paint curing oven chains and any other type of bearing/slide/gearbox applications where they are exposed to high operating temperatures and must maintain a clean lubricated surface. SYN High Temp 68 & 220 are available in Pails & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-68-SYN-High-Temp-100-Ester-Based-Multi-Purpose-Synthetic-Fluid.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	68	68	ISO Grade
	109	109	Viscosity Index
Saybolt Viscosity at 100Â°F	364 SUS	364 SUS	
Saybolt Viscosity at 210Â°F	58 SUS	58 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	74 cSt	74 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	11 cSt	11 cSt	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	>= 316 Â°C	>= 600 Â°F	
Pour Point	-31.7 Â°C	-25.0 Â°F	
Flammability Test	640	640	[Â°F] Fire Point
Flash Point	290 Â°C	554 Â°F	

Descriptive Properties	Value	Comments
SAE No.	20	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China