

Lubriplate 730-2 Aluminum Complex Multi-Purpose Grease

Category: Fluid, Lubricant, Aluminum Gellant

Material Notes:

High performance aluminum complex greases that provide high load carrying ability and AW protection with high resistance to water, steam, and other corrosive action. Available in 3 NLGI densities for a wide range of applications and temperatures. No. 730-2 is NLGI GC-LB certified. Applications: Industrial/const. equip. adverse conditions. 730 Series Greases are available in Cans, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-730-2-Aluminum-Complex-Multi-Purpose-Grease.php

| Physical Properties | Metric | English | Comments |
|--|---------|---------|----------|
| Saybolt Viscosity at 100°F | 800 SUS | 800 SUS | |
| Kinematic Viscosity at 40°C (104°F) | 151 cSt | 151 cSt | |

| Mechanical Properties | Metric | English | Comments | |
|----------------------------|--------|---------|------------------------|--|
| Penetration P(0), 1/10 mm | 265 | 265 | Unknown Amount of Work | |
| Penetration P(60), 1/10 mm | 295 | 295 | Unknown Amount of Work | |

| Thermal Properties | Metric | English | Comments | |
|----------------------------------|----------|----------|-------------------|--|
| Minimum Service Temperature, Air | -23.3 °C | -10.0 °F | Approx. Cold test | |
| Dropping Point | 293 °C | 560 °F | ASTM Test | |

| Descriptive Properties | Value | Comments |
|--------------------------------------|-------|----------|
| Antiwear (AW)/ Extreme Pressure (EP) | AW/EP | |
| NLGI Grade | 2 | |
| Rust/Oxidative Additives | YES | |
| Water Resistant | YES | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China