

Lubriplate 78 Cooker Oil Food Machinery Oil

Category : Fluid , Lubricant

Material Notes:

Class H-2** oil, for use in Manzel lubricators for A-B cookers and sterilizers, FMC cookers. Corrosion and oxidation resistant. Available in Bottles, Jugs, Pails, 1/4 Drums and Drums. H-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. **H-2 Class lubricants may be used as a lubricant or anti-rust agent on equipment in which there is no possibility of the lubricated part contacting the edible product. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-78-Cooker-Oil-Food-Machinery-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	99	99	Viscosity Index
	150	150	ISO Grade
Saybolt Viscosity at 100Â°F	850 SUS	850 SUS	
Saybolt Viscosity at 210Â°F	82 SUS	82 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	164 cSt	164 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	15 cSt	15 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-28.9 Â°C	-20.0 Â°F	
Flammability Test	565	565	[Â°F] Fire Point
Flash Point	246 Â°C	475 Â°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	90	
SAE No.	40	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China