

## Lubriplate CP-8A Petroleum-Based Gear, Bearing, & Recirculating Oil

Category : Fluid , Lubricant

**Material Notes:**

This non-EP (Extreme Pressure) oil is manufactured with acidless tallow as required to meet AGMA specification 8A Comp. It is recommended for use in cone drives and double-enveloping worm gear drives. CP-8A is available in Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-CP-8A-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-CP-8A-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	95	95	Viscosity Index
	1000	1000	ISO Grade
Saybolt Viscosity at 100Å°F	4950 SUS	4950 SUS	
Saybolt Viscosity at 210Å°F	230 SUS	230 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	950 cSt	950 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	47 cSt	47 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	1.67 Å°C	35.0 Å°F	
Flammability Test	600	600	[Å°F] Fire Point
Flash Point	288 Å°C	550 Å°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	250	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China