

Lubriplate EMB Lithium-Polymer Type Grease For Special Applications / Conditions

Category: Fluid, Lubricant, Lithium Gellant

Material Notes:

Lithium polymer type grease developed specifically for the lubrication of electric motor bearings, fans, and other high speed grease type ball and roller bearings. Applications: Electric motor bearings, fans, air handlers. EMB is available in Cartridges, Cans, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-EMB-Lithium-Polymer-Type-Grease-For-Special-Applications-Conditions.php

| Physical Properties | Metric | English | Comments |
|-------------------------------------|---------|---------|----------|
| Saybolt Viscosity at 100°F | 500 SUS | 500 SUS | |
| Kinematic Viscosity at 40°C (104°F) | 100 cSt | 100 cSt | |

| Mechanical Properties | Metric | English | Comments | |
|----------------------------|--------|---------|------------------------|--|
| Penetration P(0), 1/10 mm | 265 | 265 | Unknown Amount of Work | |
| Penetration P(60), 1/10 mm | 295 | 295 | Unknown Amount of Work | |

| Thermal Properties | Metric | English | Comments | |
|----------------------------------|----------|----------|-------------------|--|
| Minimum Service Temperature, Air | -28.9 °C | -20.0 °F | Approx. Cold test | |
| Dropping Point | 199 °C | 390 °F | ASTM Test | |

| Descriptive Properties | Value | Comments |
|--------------------------------------|-------|----------|
| Antiwear (AW)/ Extreme Pressure (EP) | AW/EP | |
| NLGI Grade | 2 | |
| Rust/Oxidative Additives | YES | |
| Water Resistant | YES | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China