

## Lubriplate HP-2 Poly Polyurea-Thickened Type Grease For Special Applications / Conditions

Category : Fluid , Lubricant , Urea Gellant

### Material Notes:

Polyurea-thickened type grease formulated with the highest quality paraffinic base oils available. Excellent for high speed electric motor bearings and other industrial applications. Applications: Electric motor bearings. Poly HP-2 is available in Cartridges, Pails & 1/4 Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-HP-2-Poly-Polyurea-Thickened-Type-Grease-For-Special-Applications-Conditions.php](http://www.lookpolymers.com/polymer_Lubriplate-HP-2-Poly-Polyurea-Thickened-Type-Grease-For-Special-Applications-Conditions.php)

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100Â°F	650 SUS	650 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	128 cSt	128 cSt	

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	265	265	Unknown Amount of Work
Penetration P(60), 1/10 mm	295	295	Unknown Amount of Work

Thermal Properties	Metric	English	Comments
Dropping Point	260 Â°C	500 Â°F	ASTM Test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW	
NLGI Grade	2	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China