

## Lubriplate Heavy G.S.. Lithium Based Grease For Open Gearing

Category: Fluid, Lubricant, Lithium Gellant

## **Material Notes:**

Lithium-based open gear grease made for all types of open gears. Available in 4 formulas for a variety of conditions and temperatures.

Applications: Open gears, normal conditions. Gear Shield Series Greases are available in Cans, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Lubriplate-Heavy-GS-Lithium-Based-Grease-For-Open-Gearing.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	2000 SUS	2000 SUS	
Kinematic Viscosity at 40°C (104°F)	432 cSt	432 cSt	

Mechanical Properties	Metric	English	Comments	
Penetration P(0), 1/10 mm	265	265	Unknown Amount of Work	
Penetration P(60), 1/10 mm	295	295	Unknown Amount of Work	

Thermal Properties	Metric	English	Comments
Minimum Service Temperature, Air	-12.2 °C	10.0 °F	Approx. Cold test
Dropping Point	185 °C	365 °F	ASTM Test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW	
NLGI Grade	2	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China