

Lubriplate PM 500 White Oil USP Mineral -Based Food Machinery Grade

Category : Fluid , Lubricant

Material Notes:

This oil contains emulsifying agents that wet the lubricated surfaces and provide an oily film for the moving parts. Used very successfully on pear machines. Available in Bottles, Jugs, Pails, 1/4 Drums and DrumsH-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-PM-500-White-Oil-USP-Mineral-Based-Food-Machinery-Grade.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	86	86	Viscosity Index
	100	100	ISO Grade
Saybolt Viscosity at 100Å°F	560 SUS	560 SUS	
Saybolt Viscosity at 210Å°F	64 SUS	64 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	101 cSt	101 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	11 cSt	11 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-20.6 Å°C	-5.00 Å°F	
Flammability Test	485	485	[Å°F] Fire Point
Flash Point	216 Å°C	420 Å°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	80	
SAE No.	30	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China