

Lubriplate SYN LUBE 680 PAO-Based Multi-Purpose Synthetic Fluid

Category : Fluid , Lubricant , Polyalphaolefin (PAO)

Material Notes:

PAO-based zinc free fluids formulated with state of the art additives to provide outstanding performance over extended drain intervals. Applications: Syn-Lube 150, 220, 320, 460 & 680 are recommended for many types of rotary screw and piston type air compressors, hydraulic systems, blowers, and turbine oil applications. Available in Jugs, Pails, 1/4 Drums and Drums Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-SYN-LUBE-680-PAO-Based-Multi-Purpose-Synthetic-Fluid.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	170	170	Viscosity Index
	680	680	ISO Grade
Saybolt Viscosity at 100Â°F	3384 SUS	3384 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	705 cSt	705 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	68 cSt	68 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-42.8 Â°C	-45.0 Â°F	
Flammability Test	580	580	[Â°F] Fire Point
Flash Point	291 Â°C	555 Â°F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China